DATASHEET

1/17/2012

Fema Part Number

GM800480X-70-TTX2NLW-TP	
Description	7.0" Full Color TFT Display
	800 x 480 Resolution
	Brightness = 320 nits (Typical)
	Integrated Resistive Touch Panel

Fema Electronics Corporation:

17815 Newhope Street, Suite G, Fountain Valley, CA 92708 Tel: 714-825-0140

Please visit our website www.femaelectronics.com or email us at tft@femacorp.com

General Features of GM800480X-70-TTX2NLW-TP

Parameter	Specifications
Screen Size	7” (Diagonal)
Display Resolution	800 RGB X 480 pixels
Display Mode	Normally White, Transmissive
Outline Dimension	164.9 (W) X 100.0 (H) X 6.9 (D) mm
Active Area	154.1 X 85.9 mm
Dot Pitch	64.2 (W) X 179.0 um
Viewing Angle	6 o’clock
Interface Type	TTL Digital
Color Depth	16 million (8 bits per color)
Brightness	400 nits (typical @ 180mA)
LED Driver	Not included
Touch Panel	Optional 4 wire, 5 wire resistive or capacitive
Mounting Bracket	Optional
Weight	150 grams
Power Consumption	1.674 W (Backlight) 0.226W (Panel)

Typical Operating Conditions

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Power voltage	DV_{DD}	3.0	3.3	3.6	V	Note 2
	AV_{DD}	10.2	10.4	10.6	V	
	V_{GH}	15.3	16.0	16.7	V	
	V_{GL}	-7.7	-7.0	-6.3	V	
Input signal voltage	V_{COM}	3.8	4.0	4.2	V	
Input logic high voltage	V_{IH}	0.7 DV_{DD}	-	DV_{DD}	V	Note 3
Input logic low voltage	V_{IL}	0	-	0.3 DV_{DD}	V	

Absolute Maximum Ratings

Item	Symbol	Values		Unit	Remark
		Min.	Max.		
Power voltage	DV_{DD}	-0.3	5.0	V	
	AV_{DD}	6.5	13.5	V	
	V_{GH}	-0.3	40.0	V	
	V_{GL}	-20.0	0.3	V	
	V_{GH}-V_{GL}	-	40.0	V	
Operation Temperature	T_{OP}	-30	85	℃	
Storage Temperature	T_{ST}	-30	85	℃	
LED Reverse Voltage	V_R	-	1.2	V	Each LED Note 2
LED Forward Current	I_F	-	25	mA	Each LED

Note 1: The absolute maximum rating values of this product are not allowed to be exceeded at any times. Should a module be used with any of the absolute maximum ratings exceeded, the characteristics of the module may not be recovered, or in an extreme case, the module may be permanently destroyed.

Note 2: V_R Conditions: Zener Diode 20mA

Pin Assignment

Pin No.	Symbol	I/O	Function	Remark
1	V_{LED+}	P	Power for LED backlight (Anode)	
2	V_{LED+}	P	Power for LED backlight (Anode)	
3	V_{LED-}	P	Power for LED backlight (Cathode)	
4	V_{LED-}	P	Power for LED backlight (Cathode)	
5	GND	P	Power ground	
6	V_{COM}	I	Common voltage	
7	DV_{DD}	P	Power for Digital Circuit	
8	MODE	I	DE/SYNC mode select	Note 1
9	DE	I	Data Input Enable	
10	VS	I	Vertical Sync Input	
11	HS	I	Horizontal Sync Input	
12	B7	I	Blue data(MSB)	
13	B6	I	Blue data	
14	B5	I	Blue data	
15	B4	I	Blue data	
16	B3	I	Blue data	
17	B2	I	Blue data	
18	B1	I	Blue data	Note 2
19	B0	I	Blue data(LSB)	Note 2
20	G7	I	Green data(MSB)	
21	G6	I	Green data	
22	G5	I	Green data	
23	G4	I	Green data	
24	G3	I	Green data	
25	G2	I	Green data	

26	G1	I	Green data	
27	G0	I	Green data(LSB)	Note 2
28	R7	I	Red data(MSB)	
29	R6	I	Red data	
30	R5	I	Red data	
31	R4	I	Red data	
32	R3	I	Red data	
33	R2	I	Red data	
34	R1	I	Red data	Note 2
35	R0	I	Red data(LSB)	Note 2
36	GND	P	Power Ground	
37	DCLK	I	Sample clock	Note 3
38	GND	P	Power Ground	
39	L/R	I	Left / right selection	Note 4,5
40	U/D	I	Up/down selection	Note 4,5
41	V_{GH}	P	Gate ON Voltage	
42	V_{GL}	P	Gate OFF Voltage	
43	AV_{DD}	P	Power for Analog Circuit	
44	RESET	I	Global reset pin. Normally Pull High	Note 6
45	NC	-	No connection	
46	V_{COM}	I	Common Voltage	
47	DITHB	I	Dithering function	Note 7
48	GND	P	Power Ground	
49	NC	-	No connection	
50	NC	-	No connection	

I: input, O: output, P: Power

Note 1: DE/SYNC mode select. Normally pull high.
When select DE mode, MODE=”1”, VS and HS must pull high.
When select SYNC mode, MODE= ”0”, DE must be grounded.

Note 2: When input 18 bits RGB data, the two low bits of R,G and B data must be grounded.

Note 3: Data shall be latched at the falling edge of DCLK.

Current Consumption

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Current for Driver	I_{GH}	-	0.2	1.0	mA	V_{GH} =16.0V
	I_{GL}	-	0.2	1.0	mA	V_{GL} = -7.0V
	IDV_{DD}	-	4.0	10	mA	DV_{DD} =3.3V
	IAV_{DD}	-	20	50	mA	AV_{DD} =10.4V

Backlight Driving Conditions

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Voltage for LED backlight	V_L	8.7	9.3	9.9	V	Note 1
Current for LED backlight	I_L	170	180	200	mA	
LED life time	-	20,000	-	-	Hr	Note 2

Note 1: The LED Supply Voltage is defined by the number of LED at Ta=25℃ and I_L =180mA.

Note 2: The “LED life time” is defined as the module brightness decrease to 50% original brightness at Ta=25℃ and I_L =180mA. The LED lifetime could be decreased if operating I_L is lager than 180mA.

Power Sequence

a. Power on:



DV_{DD}→VGL→VGH→Data→B/L

b. Power off:



B/L→Data→VGH→VGL→DV_{DD}

Note: Data include R0~R7, B0~B7, GO~G7, U/D, L/R, DCLK, HS,VS,DE.

Timing Characteristics

AC Electrical Characteristics

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
HS setup time	T_{hst}	8	-	-	ns	
HS hold time	T_{hhd}	8	-	-	ns	
VS setup time	T_{vst}	8	-	-	ns	
VS hold time	T_{vhd}	8	-	-	ns	
Data setup time	T_{dsu}	8	-	-	ns	
Data hole time	T_{dhd}	8	-	-	ns	
DE setup time	T_{esu}	8	-	-	ns	
DE hole time	T_{ehd}	8	-	-	ns	
DV_{DD} Power On Slew rate	T_{POR}	-	-	20	ms	From 0 to 90% DV_{DD}
RESET pulse width	T_{Rst}	1	-	-	ms	
DCLK cycle time	T_{coh}	20	-	-	ns	
DCLK pulse duty	T_{cwh}	40	50	60	%	

Data Input Format



Figure 3. 1 Horizontal input timing diagram.



Figure 3. 2 Vertical input timing diagram.

Timing

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Horizontal Display Area	thd	-	800	-	DCLK	
DCLK Frequency	fclk	26.4	33.3	46.8	MHz	
One Horizontal Line	th	862	1056	1200	DCLK	
HS pulse width	thpw	1	-	40	DCLK	
HS Blanking	thb	46	46	46	DCLK	
HS Front Porch	thfp	16	210	354	DCLK	

Item	Symbol	Values			Unit	Remark
		Min.	Typ.	Max.		
Vertical Display Area	tvd	-	480	-	TH	
VS period time	tv	510	525	650	TH	
VS pulse width	tvpw	1	-	20	TH	
VS Blanking	tvb	23	23	23	TH	
VS Front Porch	tvfp	7	22	147	TH	

Optical Characteristics

Item	Symbol	Condition	Values			Unit	Remark
			Min.	Typ.	Max.		
Viewing angle (CR≥ 10)	θ_L	Φ=180°(9 o'clock)	60	70	-	degree	Note 1
	θ_R	Φ=0°(3 o'clock)	60	70	-		
	θ_T	Φ=90°(12 o'clock)	40	50	-		
	θ_B	Φ=270°(6 o'clock)	60	70	-		
Response time	T_{ON}	Normal θ=Φ=0°	-	10	20	msec	Note 3
	T_{OFF}		-	15	30	msec	Note 3
Contrast ratio	CR		400	500	-	-	Note 4
Color chromaticity	W_X		0.26	0.31	0.36	-	Note 2 Note 5 Note 6
	W_Y		0.28	0.33	0.38	-	
Luminance	L		256	320	-	cd/m²	Note 6
Luminance uniformity	Y_U		70	75	-	%	Note 7

Test Conditions:

1. DV_{DD}=3.3V, I_L=180mA (Backlight current), the ambient temperature is 25℃.
2. The test systems refer to Note 2.

Reliability

Item	Test Conditions	Remark
High Temperature Storage	Ta = 85℃ 240hrs	Note 1，Note 4
Low Temperature Storage	Ta = -30℃ 240hrs	Note 1，Note 4
High Temperature Operation	Ts = 85℃ 240hrs	Note 2，Note 4
Low Temperature Operation	Ta = -30℃ 240hrs	Note 1，Note 4
Operate at High Temperature and Humidity	+60℃, 90%RH 240hrs	Note 4
Thermal Shock	-30℃/30 min ~ +85℃/30 min for a total 100 cycles, Start with cold temperature and end with high temperature.	Note 4
Vibration Test	Frequency range:10~55Hz Stroke:1.5mm Sweep:10Hz~55Hz~10Hz 2 hours for each direction of X. Y. Z. (6 hours for total)	
Mechanical Shock	100G 6ms,±X, ±Y, ±Z 3 times for each direction	
Package Vibration Test	Random Vibration : 0.015G*G/Hz from 5-200HZ, -6dB/Octave from 200-500HZ 2 hours for each direction of X. Y. Z. (6 hours for total)	
Package Drop Test	Height:60 cm 1 corner, 3 edges, 6 surfaces	
Electro Static Discharge	± 2KV, Human Body Mode, 100pF/1500Ω	

Note 1: Ta is the ambient temperature of samples.
Note 2: Ts is the temperature of panel's surface.
Note 3: In the standard condition, there shall be no practical problem that may affect the display function. After the reliability test, the product only guarantees operation, but don't guarantee all of the cosmetic specification.
Note 4: Before cosmetic and function test, the product must have enough recovery time, at least 2 hours at room temperature.

7. OUTLINE DRAWING